

Vlieskleber

Description of material

Kind of material:

ready-for-use glue based on dispersion binder, to be used for technical glass-fleece or cellulose-fleece (with or without pigments) which will be painted over. It is ready-for-use, solvent-free and for interior use only. Its outstanding feature is the quick and smooth application combined with a very even spreading.

Application area:

for interior use on new and old solid undergrounds, such as mineral stucco, concrete, gypsum board (without lignin marks). Special adhesive for technical glass-fleece or cellulose-fleece, which should be painted over.

Binding agent:

special resin dispersion

Colour:

clear

Specific gravity:

1.0 g/cm³

pH value:

alkaline 9

Diluting agent:

water

Viscosity:

slightly thixotropic

Application characteristics

Application:

brush / roller / spray (airless).

Underground:

needs to be clean, dry, and solid. Otherwise use JONAS Hydro-Haft-& Tiefgrund first to consolidate the underground. For underground treatment and application VOB, part C, DIN 18363 must be observed.

Coating build-up:

roller: without dilution.
airless-spray: without dilution.
pasting maching: use Vlieskleber without dilution. Find the optimum quantity of Vlieskleber with the help of a piece of technical glass-fleece or cellulose fleece.

Spreading rate:

approx. 150 – 250 g/m² on smooth underground (if necessary test it on the wall).

Application temperature:

at least + 5°C (Degrees Celsius) for air and underground during application and drying.

Drying:

the surface of the coating is dry and can be painted over after 8 - 10 hours (at a temperature of 20 °C and a relative atmospheric humidity of 65 %).

Cleaning of tools:

clean with water immediately after use.

General information

Storage:

cool, but not freezing.

Packaging:

16 kg

Transport:

the product is not classified for transport.

Safety:

the product is not classified for health and environmental risks.

Product code:

M-DF01

Ingredients:

resin dispersion, starch derivative, water, additives, preservative.

Advice:

Keep out of reach of children. Wear appropriate respiratory protection (full mask / half mask equipped with filter type A2/P2). Avoid eating, drinking and smoking during use of the product. Ensure good ventilation during and after application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains or water courses. Advice for people suffering from isothiazolinone allergy under phone-no.: +49(0)2058/789-0.

Waste disposal:

empty containers can be disposed for recycling. Any dried residues of material can be disposed of as construction waste or together with domestic garbage. Containers with liquid material residues must be disposed of according to local regulations. For further information please contact your local waste authority.