

Haftgrund

Description of material

Kind of material:

white primer without structuring grain, for exterior and interior use. Can be used as primer, adhesion promoter and for strengthening substrates such as gypsum plasterboards. For all following coatings with dispersion paint and silicone or silicate paint. Levels the surface for following painting or wallpaper. Solvent-free.

Gloss level:

matt

Application area:

for exterior and interior use on good, solid new and old undergrounds such as stucco, concrete, gypsum board. As primer for following coating with dispersion paint, silicone or silicate paint and for wallpapers.

Binding agent:

special resin dispersion

Colour:

white

Content of solids:

approx. 68 %

Specific gravity:

1.61 g/cm³

pH value:

alkaline 9

Diluting agent:

water

Viscosity:

slightly thixotropic

Application characteristics

Application:

brush, roller, spray (airless).

Underground:

needs to be clean, dry, and solid. For highly absorbent substrates use JONAS Hydro-Haft-& Tiefgrund at the beginning to consolidate the underground. For underground treatment and application VOB, part C, DIN 18363 must be observed.

Structure of application:

priming coat: use product without dilution.

Quantity per application:

approx. 200 ml/m² on smooth underground (if necessary test on the wall).

Application temperature:

at least + 5°C (Degrees Celsius) for air and underground during application and drying.

Drying:

the surface of the coating is dry and can be painted over after 8 - 10 hours (at a temperature of 20 °C and a relative atmospheric humidity of 65 %).

Tinting:

product can be tinted with standard tinting paints.

Cleaning of tools:

clean with water immediately after use.

Storage:

cool, but not freezing.

General information

Packaging:

12.5 l / 5 l

Transport:

the product is not classified for transport.

Safety:

the product is not classified for health and environmental risks.

Product code:

M-GP01

Remark:

application, drying and coating properties might be influenced by weather conditions (i.e. heat, wind, sun etc.).

VOC contents:

EU-Limit for the product Kat. A/h: 30 g/l (2010). This product contains < 1 g/l VOC.

Ingredients:

special resin dispersion, white pigments, calcium carbonate, water, additives, preservative.

Advice:

Keep out of reach of children. Wear appropriate respiratory protection (full mask / half mask equipped with filter type A2/P2). Avoid eating, drinking and smoking during use of the product. Ensure good ventilation during and after application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains or water courses. Advice for people suffering from isothiazolinone allergy under phone-no.: +49(0)2058/789-0.

Waste disposal:

empty containers can be disposed for recycling. Any dried residues of material can be disposed of as construction waste or together with domestic garbage. Containers with liquid material residues must be disposed of according to local regulations. For further information please contact your local waste authority.